



2001NdU

Nominal Diameter	8 " / 20 cm
Rated Impedance	8
Sensitivity	92 dB SPL
Power Handling Capacity	120 W AES
SPL max (continuous)	110 dB SPL
Usable frequency range	60 - 4000 Hz
Speaker net mass	1.7 kg

8 inches low-mid driver



Architecture highlights :

- Neodymium magnet system with symmetric BL(x) and Le(x)
- Natural convection Intercooler System
- Double side coated diaphragm (Tropical withstanding)
- High compliance double half-roll Fabric Surround

Motor architecture

Magnet material	-	Nd
Voice coil diameter	mm	38
Voice coil length	mm	14
Air gap height	mm	6

Typical characteristics


Rated impedance	Z	Ω	8
Half space sensitivity (1W@1m)	-	dB SPL	92.0
Usable freq. range	-	Hz	60 - 4000
Power handling capacity (AES)	-	W	120
Max Sound Pressure Level	SPL _{max}	dB SPL	110
Min. impedance modulus	Z _{min}	Ω@Hz	6.1@320
Voice-coil inductance @ 1kHz	Le _{1k}	mH	0.516
Voice-coil inductance @ 10kHz	Le _{10k}	mH	0.303
BL product	BL	N/A	9.5
Moving mass	M _{ms}	kg	0.0210

Thiele-Small parameters

Resonance frequency	F _s	Hz	77 (±11)
DC Resistance	Re	Ω	5.4 (±0.5)
Mechanical quality factor	Q _{ms}	1	4.07
Electrical quality factor	Q _{es}	1	0.61
Total quality factor	Q _{ts}	1	0.53
Suspension compliance	C _{ms}	10 ⁻⁶ .m/N	200
Effective piston area	S _d	m ²	0.0219
Equivalent Cas air load	V _{as}	m ³	0.0138
Max linear excursion	X _{max}	mm	± 5.5
Linear displacement volume	V _d	10 ⁻³ .m ³	0.1205
Reference efficiency	η ₀	%	1.0
Unity load volume	V _{as} .Q _{ts} ²	10 ⁻³ .m ³	3.9

Absolute maximum ratings

Short term max. input voltage	V _{max}	V	60
Max.excursion before damage	X _{dam}	mm	± 13.0
Ambient operating temperature	T _a	°C	-10 to +50
Storage temperature		°C	-20 to +70
Environmental withstanding			Tropical



Mounting information

Air volume occupied by the driver	10 ⁻³ .m ³	0.50
Speaker net mass	kg	1.70
Baffle cut-out diameter (front mounting)	mm	185.0
Bolt number & Metric diameter	-	4x M5
Bolt circle diameter	mm	217.0
Max overall dimension (on ears)	mm	234.0
Max overall dimension (out of ears)	mm	205.0
Flange height	mm	9.5
Max magnet diameter	mm	74.0
Max depth (front mounting)	mm	88.5
Recommended reflex box	Lts / Hz	-
Electrical connection		6.3x0.8 Faston



2001NdU

8 inches low-mid driver


SPL curves measured on CEI standard baffle :

- . at 25 cm, normalised 1 m
- . at 1 m for reference
- . Graph amplitude = 60 dB (PHL Audio standard)



HD curve measured on CEI standard baffle :

- . at 1 meter
- . at power = $P_{AES} / 4$
- . Graph amplitude 0.01 % to 100 % (PHL Audio standard for $P_{AES}/4$)



Non linear curves measured thanks to Klippel software and hardware, in free air

